



TECHNICAL DATA SHEET

SKIRTING BOARDS

MATERIAL

Extruded polystyrene (XPS)

COLLECTION AND DIMENSIONS

Collection	Index	Dimensions (W x D x L)
ESSENZA S	LP-ESSENZA S	60x14x2000mm
ESSENZA M	LP-ESSENZA M	80x14x2000mm
ESSENZA L	LP-ESSENZA L	100x14x2000mm
ARCHE S	LP-ARCHE S	60x14x2000mm
ARCHE M	LP-ARCHE M	80x14x2000mm
ARCHE L	LP-ARCHE L	100x14x2000mm
LINEA M	LP-LINEA M	80x15x2000mm
LINEA L	LP-LINEA L	100x15x2000mm
QUADRO M	LP-QUADRO M	80x15x2000mm
QUADRO L	LP-QUADRO L	100x15x2000mm
STELLA M	LP-STELLA M	80x13,5x2000mm
STELLA L	LP-STELLA L	100x13,5x2000mm

PRODUCT FEATURES

- Made of lightweight, durable and moisture – resistant XPS material.
- Resistant to impacts and scratches.
- Intended for indoor use.
- Available in various profiles to match interior styles : classic, modern and minimalist.
- 100% recyclable product



TECHNICAL DATA SHEET

SKIRTING BOARDS

INSTALLATION RECOMMENDATIONS

- Installation using mounting adhesive (e.g., Lamelio adhesive or other hybrid polymer adhesive, free of solvents and isocyanates).
- Install on a smooth, clean, and dry surface to ensure proper adhesion.
- Cutting is possible using a hand saw, jigsaw, or miter saw.
- For corners, a 45-degree angle cut should be used.
- Before installation, leave the boards in the room where they will be installed to equalize the temperature with the environment.

PAINTING

Lamelio skirting boards can be painted with acrylic or latex paints. Before painting, the surface should be cleaned and degreased, and for better adhesion, it should be primed.

Painting methods:

- Spray painting: For achieving a perfectly smooth surface.
- Brush or roller: Using a well-covering acrylic paint (1-2 coats recommended).

The use of solvent-based paints is not recommended.

MAINTENANCE AND CLEANING

- Use a soft, damp microfiber cloth for cleaning.
- Do not use strong detergents, bleaches, solvents, or abrasive agents.
- After cleaning, wipe the surface thoroughly with a dry cloth.
- Leaving cleaning agents on the surface may cause discoloration.

Storage and Transport

- Store in a dry place, in a horizontal position, on a flat surface.
- Protect from sunlight and heat sources.
- Avoid bending or crushing the boards during transport and storage.